

Specification	Range	Best Accuracy	
		UT39A	UT39B
DC Voltage (V)	200mV/2V/20V/200V/1000V	$\pm(0.5\%+1)$	$\pm(0.5\%+1)$
AC Voltage (V)	2V/20V/200V/750V	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
DC Current (A)	20 μ A/200 μ A/2mA/20mA/200mA/10A	$\pm(0.8\%+1)$	
	20 μ A/2mA/20mA/200mA/10A		$\pm(0.8\%+1)$
AC Current (A)	200 μ A/20mA/200mA/10A	$\pm(1\%+3)$	
	2mA/200mA/10A		$\pm(1\%+3)$
Resistance (Ω)	200 Ω /2K Ω /20K Ω /200K Ω /2M Ω /200M Ω	$\pm(0.8\%+1)$	
	200 Ω /2K Ω /20K Ω /2M Ω /20M Ω /200M Ω		$\pm(0.8\%+1)$
Capacitance (F)	2 μ F	$\pm(4\%+3)$	
	2nF/200nF/20 μ F		$\pm(4\%+3)$

Features			
Display Count		1999	1999
Manual Range		✓	✓
Diode		✓	✓
Transistor		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Input Impedance for DCV	Around 10M Ω	✓	✓

General Characteristic	
Power	9V Battery (6F22)
LCD Size	61mm×32mm
Product Color	Red and Grey
Product Net Weight	310g (Including Holster)
Product Size	172mm×83mm×38mm
Standard Accessories	Battery, Test Lead,Holster
Standard Individual Packing	Gift Box, English Manual