





Models	LM600	LM1000	LM1500	LM2000
Page	140	140	140	141
				
Distance range	5~600yd	5~1000yd	5~1500yd	2000m
Accuracy	±1yd ± DX 0.2%	±1yd ± DX 0.2%	±1yd ± DX 0.2%	± (0.3m+0.001×Dm)
Measuring unit	yd	yd	yd	m/yd/ft
Magnification	7X	7X	7X	8X
Diameter	object lens diameter 25mm	object lens diameter 25mm	object lens diameter 25mm	object lens diameter 23mm eyepiece diameter 31mm exit pupil diameter 3.8mm
Height	250yd	450yd	600yd	
Height accuracy	±0.5yd	±0.5yd	±0.5yd	
Velocity range	0-300km/h	0-300km/h	0-300km/h	
Angle	±45°	±45°	±45°	-90°~90°
Angle accuracy	±1°	±1°	±1°	tilt angle accuracy ±0.5° gyroscope angle accuracy ±0.1°
Charging interface	Micro USD	Micro USD	Micro USD	Type-C
Data export				USB
Pulse laser	Harmless to eyes	Harmless to eyes	Harmless to eyes	Harmless to eyes
Fast distance measurement	●	●	●	●
LCD display	●	●	●	Black(red) bicolor R-Plcd
Auto power off	●	●	●	●
Tripod mounting hole	●	●	●	●
Power	3.7V Li-ion battery 1500mAh	3.7V Li-ion battery 1500mAh	3.7V Li-ion battery 1500mAh	2000mAh Lithium battery
Certificates	CE/UKCA	CE/UKCA	CE/UKCA	CE/UKCA

UNI-T's LM series laser rangefinders enable accurate measurement of height, distance, and angle. The new speed measurement function adopts low power pulsed laser that is safe for the eyes. LM series laser rangefinders are perfect tools for a wide variety of applications such as engineering surveying, building construction, navigation, golf, and hunting.



Distance:
5~1500yd



HD coating



Skidproof



Angle: $\pm 45^{\circ}$



6X optical
zoom telescope



Height:
0~600yd



Speed: 0~300km/h
(0~186mi/h)



Built-in
Li-ion battery



Specifications	LM600	LM1000	LM1500
Certificates	CE, UKCA		
Distance range	5~600yd	5~1000yd	5~1500yd
Height	250yd	450yd	600yd
Accuracy	$\pm 1\text{yd} \pm D \times 0.2\%$		
Magnification	6X		
Lens diameter	24mm		
Height error	$\pm 0.5\text{yd}$		
Velocity range	0-300km/h (reference only)		
Angle	$\pm 45^{\circ}$		
Angle error	$\pm 1^{\circ}$		
Pulse laser	Harmless to eyes		
Silent operation	Auto power off system		
Fast distance measurement	√		
LCD display	√		
Tripod mounting hole	√		

Characteristics	
Standard accessories	Carrying bag, hanging cord, USB interface cable, English manual
Power	3.7V Li-ion battery 1500mAh
Product size	114 x 76 x 48mm
Product net weight	230g
Standard individual packing	Gift box
Standard quantity per carton	6pcs
Standard carton measurement	350 x 315 x 112mm
Standard carton gross weight	LM600: 2.6kg; LM1000/LM1500: 2.94kg