

# BATTERY TESTERS & OHM METERS

Key Specifications	UT3513	UT3516
Resistance range	20mΩ/200mΩ/2Ω/20Ω/200Ω/2kΩ/20kΩ	20mΩ/200mΩ/2Ω/20Ω/200Ω/2kΩ/20kΩ/200kΩ/2MΩ
Resolution	1μΩ/10μΩ/100μΩ/1mΩ/10mΩ/100mΩ/1Ω/10Ω/100Ω	
Test current	1A/1A/100mA/10mA/1mA/1mA/100μA/10μA/1μA	
Testing terminal open-circuit voltage	<1V/<1V/<1V/<1V/<5V/<5V/<5V/<5V/<3V	
Measured parameter	DC resistance	
Basic accuracy	Slow: 0.1%, Medium: 0.2%	Slow: 0.05%, Medium: 0.1%, Rapid: 0.5%
Maximum reading	22000	
Range mode	Auto/manual/nominal	
Speed	Slow: 3 times/s, Medium: 18 times/s, Rapid: 60 times/s(Only for UT3516)	
Calibration	Short-circuit full range zeroing	
Sorting function	3 types of resistance and voltage input: exceeds upper limit/exceeds lower limit/within the range, 2 types of sorting result output: PASS/FAIL	
Comparing method	Absolute tolerance, percentage tolerance, direct-reading comparison	
Trigger mode	Internal, external	
Test terminal	Four-terminal measurement	
Button functions	Lock – keyboard lock, OK – screenshot	
System setup	Language: Chinese/English	
Interfaces & protocols	Handler interface, RS232, USB DEVICE and USB HOST communication interface, SCPI and Modbus protocol	
PC software	√	
Power	AC 100~240V, 50/60Hz	
Display	4.3 inch LCD	
Product size(W×H×D)	214mm x 89mm x 340mm	
Product net weight	3kg	
Standard quantity per carton	2pcs	
Standard carton size	420mm x 360mm x 405mm	
Standard carton gross weight	8.5kg	

Ordering Information	
UT3510 Series	UT3516: DC Resistance Tester (2MΩ, accuracy: 0.05%)
	UT3513: DC Resistance Tester (20kΩ, accuracy: 0.1%)
Standard Accessories	International standard power cord
	UT-L82: Kelvin test lead x1
	Temperature compensation line (only for UT3513)
Optional Accessories	Temperature compensation line