





WW158B-F01(5A/250V)




WW158B-F04E(5A/250V)




WW158B-F06E(5A/250V)




WW158B-F03E(5A/250V)




WW158B-F02E(5A/250V)




WW158B-F04-1E(10A/250V)




WW158B-F09E(5A/250V)




WW158B-F05E(5A/250V)



WW158B-F12-1E(5A/250V)



WW158B-F15E(5A/250V)



Material: Nylon 66 UL94V-2
 Current rating: 5A AC, DC Max
 Voltage Rating: 300V AC, DC Max
 Contact resistance: 15mΩ Max
 Insulation resistance: 1000MΩ Min
 Withstanding voltage: 1500V AC/Minute
 Temperature range: -25°C to +85°C
 Applicable panel thickness: 2 mm max

| Rev | Description/Date | Drawn By: Storm.li | Customer: | Third angle projection | Units: mm |
|-----|------------------|--------------------|-----------|------------------------|-----------|
|-----|------------------|--------------------|-----------|------------------------|-----------|

| | | | | | | | | | | | |
|-------|--------------------|-----------|--------------------|-----------------------------|--|----|-----|------|-------|------|-------|
| △ | Checked By: Simmon | Part No.: | WW158B-F(E) Series | General Dimension Tolerance | <table border="1"> <tr> <td>XX</td> <td>XXX</td> <td>XXXX</td> </tr> <tr> <td>±0.25</td> <td>±0.1</td> <td>±0.08</td> </tr> </table> | XX | XXX | XXXX | ±0.25 | ±0.1 | ±0.08 |
| XX | XXX | XXXX | | | | | | | | | |
| ±0.25 | ±0.1 | ±0.08 | | | | | | | | | |
| △ | Approved By: Tony | Title: | Housing | | | | | | | | |

| | |
|-----------------------------------|--|
| SGS Report No.: KA/2004/80788/A-2 | |
|-----------------------------------|--|